

## Symbols

1-D stackups. *See Tolerance analysis, 1-D*  
2-D stackups. *See Tolerance analysis, 2-D*  
3-D stackups. *See Tolerance analysis, 3-D*  
80-20 rule. *See Pareto principle*

## A

Abutting profile tolerance zone. *See Profile tolerance abutting zones*

Accuracy 18-3

Active drawing 4-30

Actual

feature 5-61

local size 5-46

mating envelope 5-41, 5-43

restraint of 5-41, 5-42

simulation of 5-43

mating local size 5-45

mating size 5-37, 5-43

minimum material envelope 5-44

restraint of 5-44

simulation of 5-44

minimum material local size 5-46

minimum material size 5-44

value 7-7

Algorithms 7-3

Alignment

between parts. *See Mating parts*

pins 24-1

error 24-3, 24-12, 24-13, 24-16, 24-17, 24-20, 24-24, 24-27

one diamond and one round/two holes 24-23, 24-25

one parallel flats and one round/two holes 24-26, 24-28

two round/hole and edge contact 24-18, 24-21

two round/hole and slot 24-14, 24-19

two round/two holes 24-11, 24-15  
types of 24-4

All around symbol 5-13, 5-150, 5-151  
comparison of US and ISO 6-7

All over note 5-150, 5-151

Allocation

by scaling/resizing/weight factor. *See Tolerance allocation by scaling/resizing/weight factor*

cost. *See Tolerance allocation by cost minimization*

cost versus tolerance. *See Cost versus tolerance allocation*

DRSS. *See Dynamic Root Sum of the Squares (DRSS) allocation*

manufacturing process. *See Tolerance allocation by manufacturing processes*

RSS. *See Root Sum of the Squares (RSS) allocation*

Six Sigma tolerance. *See Six Sigma tolerance allocation*

statistical tolerance. *See Statistical tolerance allocation*

tolerance. *See Tolerance allocation*

worst case. *See Worst case allocation*

Alternative center method 5-43, 5-52, 5-

113, 5-122, 5-123, 5-124, 5-125, 5-127

disadvantages 5-46

Level 2 adjustment 5-45

Level 3 adjustment 5-43

Level 4 adjustment 5-43

American National Standards 5-2

ASME Y14.5.1M (the "Math Standard") 5-3, 5-4, 5-23, 7-14

## I-2 Index

- ASME Y14.5M 3-2, 3-13, 3-15, 5-3, 5-4, 7-14
  - budgeting of coverage 5-3, 5-136
  - differences in standards 5-59, 5-117, 5-136, 5-145
  - discrepancies in 5-4
  - future of 5-164
  - recommendations/suggestions 5-165
- Institute (ANSI) 4-2, 5-2
- superceding 5-4
- American Society of Mechanical Engineers (ASME) 5-165, 6-2, 8-10
- Analysis
  - computer. *See Computer analysis*
  - Estimated Mean Shift. *See Estimated Mean Shift analysis*
  - Fixed fastener. *See Fixed fastener tolerance analysis*
  - Floating fastener. *See Floating fastener tolerance analysis*
  - Future of. *See Future of tolerance analysis*
  - GD&T. *See Geometric Dimensioning and Tolerancing (GD&T) analysis*
  - GR&R. *See Gage repeatability and producibility (GR&R), analysis of*
  - graphical inspection. *See Graphical inspection analysis*
  - measurement methods. *See Measurement methods analysis*
  - MRSS. *See Modified Root Sum of the Squares (MRSS) analysis*
  - process. *See Process analysis*
  - RSS. *See Root Sum of the Squares (RSS) analysis*
  - SRSS. *See Static Root Sum of the Squares (SRSS) analysis*
  - tolerance. *See Tolerance analysis*
  - worst case. *See Worst case analysis*
- Anderson-Darling test for normality 10-4
- Angle
  - 90° basic. *See Implied 90° basic angle*
  - basic. *See Basic dimension, implied dimension*
  - dimension
    - 90° implied. *See Implied 90° angle dimension*
  - erroneous wedge-shaped tolerance zone for 5-112
  - plus and minus tolerance 5-49, 5-50, 5-112
  - transition between features 5-10
- Angled
  - datum 5-75
  - feature 5-117
- Angularity tolerance 5-104
  - analysis of 9-26
  - comparison of US and ISO 6-19
  - for a cylindrical feature 5-106
  - for a width-type feature 5-106
  - symbol 5-13
- ANSI. *See American National Standards Institute (ANSI)*
- Approximation model 15-5
- Arc length symbol 5-13, 5-16
- Asea Brown Boveri Ltd. (ABB) 1-6
- ASME
  - standards 7-14
  - Y14.5. *See American National Standards ASME Y14.5M*
- Assemblability
  - worst case 5-33, 5-34, 5-35, 5-128
- Assembly 8-1, 16-8
  - clearance. *See Fixed fastener formula; Floating fastener formula; Mating parts; Maximum Material Condition (MMC), when to apply; Virtual condition boundary*
  - datum feature selection for 5-61, 5-63
  - deformation 15-5
  - drawing 4-10, 4-11, 5-19
  - drawings 4-4
  - equation. *See Gap equation*
  - for dynamic balance 5-144, 5-162
  - force 5-146
  - graph 13-4
  - interface 5-71
    - centering 5-47
  - process variation 15-4
  - restraint of parts in 5-20
  - sequence 5-64
  - shift 23-4
  - standards 26-4
  - tolerance 5-19, 9-11
  - tolerance models
    - 2-D 13-3. *See also Tolerance model, steps in creating (2-D/3-D)*
    - closed loop 13-4, 13-11, 13-13, 13-14
    - critical features 13-10

- datum paths 13-5, 13-7
- datum reference systems 13-4, 13-5
- degrees of freedom 13-5
- geometric variations 13-10, 13-11. *See also Variation*
- graph 13-4
- key characteristics 13-10
- kinematic joints 13-4, 13-5, 13-6, 13-7
- modeling 13-4
- modeling rules 13-7, 13-8
- open loop 13-4, 13-11, 13-13, 13-14
- performance requirements. *See Performance requirements*
- redundant vectors 13-12
- steps in creating. *See Tolerance model, steps in creating*
- vector loops 9-3, 11-7, 12-6, 13-8, 13-9, 13-11, 13-13, 13-14, 23-3, 23-6
- vectors. *See Vectors*
- variation sources 13-2
- Attribute
  - data 10-2
  - process capability models 17-7
- Automated verification 16-10
- Automation 15-2
- Auxiliary
  - dimension
    - comparison of US and ISO 6-10
  - view 4-16
- Average diameter 5-56
- Axis
  - datum. *See Datum axis*
  - feature, control of. *See Feature control frame*
- B**
- Baldrige. *See Malcolm Baldrige National Quality Award*
- Bar stock 5-29
- Base line dimensioning 5-116
- Basic
  - angle 5-19, 5-104. *See also Angle, basic; Basic dimension*
  - dimension 5-17
    - defining a basic profile 5-145
    - established by general note 5-163
    - for profile boundary offset 5-147
    - frame 5-17
    - implied. *See Implied basic dimension*
    - limiting length or area of tolerance zone 5-57. *See also Limited length/area indication*
    - locating a datum target 5-94
    - locating termination of tolerance zone 5-152
    - locating true position. *See True position methods for establishing*
    - shown as reference 5-18
    - symbol (frame) 5-17
    - zero implied. *See Implied basic dimension*
- dimension symbol
  - comparison of US and ISO 6-7
- profile 5-147. *See also Profile tolerance*
  - defined by basic dimensions 5-145
  - defined by CAD/CAM model 5-147
  - defined by grid system 5-147
  - defined by mathematical formula 5-147
  - showing termination of tolerance zone 5-152
  - tolerance boundary offset from 5-147
  - tool path along 5-147, 5-153
  - size 5-48
- Beta distribution 10-6
- Between symbol 5-13, 5-16, 5-150, 5-152
  - comparison of US and ISO 6-7
- Bidirectional positional tolerance 5-122, 5-125, 5-126
- Bilateral profile tolerance. *See Profile tolerance, bilateral*
  - equal. *See Profile tolerance, equal-bilateral*
  - analysis of 9-34
  - unequal. *See Profile tolerance, unequal bilateral*
  - analysis of 9-35
- Binomial distribution 10-8
- Bolt circle 5-115, 5-116
- Bonus tolerance
  - at LMC 5-44
  - at MMC 5-43
- Boundary
  - at LMC 5-23, 5-25
  - at MMC 5-23, 5-24, 5-25
  - inner, outer 5-46
  - of perfect form 5-27
    - at LMC 5-28, 5-29
    - at MMC 5-27
    - not required 5-29, 5-30, 5-39

## I-4 Index

- resultant condition. *See Resultant condition boundary*
- size limit. *See Size limit boundary*
- spherical 5-22
- tapered 5-121
- tolerance 5-14
- virtual condition. *See Virtual condition boundary*
- Bounded feature 5-11, 5-126
  - as a datum feature 5-77, 5-79, 5-82
  - composite profile tolerance for a single feature 5-156
  - datum targets applied to 5-99
  - positional tolerance for. *See Positional tolerance for a bounded feature*
- Broken-out section 4-19
- C**
- CAD. *See Computer Aided Design (CAD)*
- CAD/CAM. *See Computer Aided Design (CAD); Computer Aided Manufacturing (CAM)*
- CAE. *See Computer Aided Engineering (CAE)*
- CAM. *See Computer Aided Manufacturing (CAM)*
- Candidate
  - datum 5-90, 7-8
    - reference 7-8
  - datum reference frame 5-90
- Cartesian coordinates 5-69, 5-70
- Casting 16-18
  - drawing 4-5
- Castings/forgings 5-64, 5-151
- CAT 15-6, 15-12, 15-13, 15-14. *See also Computer Aided Tolerancing (CAT)*
- Cauchy distribution 10-6
- Center
  - line 5-10, 5-109.
    - implied 90° angle 5-19
  - marks 4-4
  - method
    - alternative. *See Alternative center method*
  - plane 5-10, 5-41, 5-89
    - control of. *See Feature control frame*
    - control of feature 5-106, 5-113, 5-119, 5-122
    - datum 19-12
    - derived 5-38, 5-40
      - establishing a datum from a feature 5-65
      - establishing a datum from feature 5-89
      - feature 5-41
      - point 5-38, 5-41, 5-113
- Centering 5-47. *See also Regardless of Feature Size (RFS), when to apply*
- Central tolerance zone 5-25, 5-38, 5-39
- Certification of GD&T professionals 5-3
- Chain
  - dimensioning 5-116
  - line 5-57, 5-65, 5-119, 5-143
- Characteristic symbol. *See Geometric characteristic symbol*
- Circular runout tolerance 5-138, 5-139, 5-141, 5-144
  - symbol 5-13
- Circularity (roundness) tolerance 5-53, 7-9
  - analysis of 9-25
  - control by limits of size 5-22
  - control of lobes. *See Lobes, circularity control*
  - for a nonspherical feature 5-53
  - for a spherical feature 5-54, 5-55
  - in the free state 5-56
  - not affecting size, taper, or straightness 5-54, 5-55
  - not modifiable to MMC or LMC 5-55
  - symbol 5-13
  - with average diameter 5-56
- Clearance fit. *See Fixed fastener formula; Floating fastener formula; Mating parts; Maximum Material Condition (MMC), when to apply; Virtual condition*
- Clocking 5-87, 5-97
- Closed loop. *See Assembly tolerance model, closed loop*
- CM/PDM. *See Configuration Management/Product Data Management*
- CMM. *See Coordinate measuring machine (CMM)*
- Co-datums. *See Hyphenated co-datums*
- Coaxial/coplanar pattern of features 5-103, 5-136, 5-154
- Combined controls 5-162
- Company vault 16-12
- Component
  - deformation 15-5

- libraries 16-9
- Composite tolerance
  - positional. *See Positional tolerance, pattern control, composite*
  - analysis of 9-32
  - comparison of US and ISO 6-20
  - verification 18-10
- profile
  - analysis of 9-36
  - for a pattern of features. *See Profile tolerance, composite, for a pattern of features*
  - for a single feature. *See Profile tolerance, composite, for a single feature*
- rules for. *See Rules for pattern control, composite*
- Computer
  - Aided Design (CAD) 15-2, 15-5, 15-13, 16-2
  - Aided Design (CAD)/Manufacturing (CAM) 5-147
  - Aided Engineering (CAE) 16-2
  - Aided Tolerancing (CAT) 15-2
  - analysis 5-32
- Concentricity tolerance 5-144, 5-158, 5-160, 5-161
  - analysis of 9-33
  - comparison of US and ISO 6-25
  - comparison with other methods 5-160
  - control of lobes. *See Lobes, concentricity control*
  - for multifold symmetry 5-160
  - symbol 5-13
- Concurrent
  - engineering 15-9
  - index 10-12
- Condition
  - material. *See Material condition*
  - resultant. *See Resultant condition*
  - virtual. *See Virtual condition*
- Configuration
  - layout 4-30
  - Management 16-11
  - Management/Product Data Management 15-13
- Conical
  - surface
    - control of 5-60, 5-153
    - tolerance zone 5-121
- Constraints 7-4
- Contribution chart. *See Percent contribution chart*
- Control
  - combined. *See Combined controls*
  - extent of profile tolerance. *See Extent of profile tolerance*
  - four levels of. *See Levels of control*
- Controlled radius 5-59
  - symbol 5-13, 5-16, 5-59
  - comparison of US and ISO 6-7
  - tolerance 5-59
- Conventional
  - breaks 4-22
  - practices 4-23
- Coordinate
  - dimensioning 5-9
  - measuring machine (CMM) 5-90, 5-164, 7-2, 20-1
  - system
    - Cartesian. *See Cartesian coordinates*
    - polar. *See Polar coordinate system*
    - rectangular. *See Rectangular coordinate system*
- Coplanarity 5-137
  - positional tolerance for 5-137
  - profile tolerance for 5-154
- Corporate standards 16-10
- Cost 5-4, 5-8
  - appraisal 1-4
  - failure 1-4
  - minimization/optimization 14-1, 14-12
  - prevention 1-4
  - versus tolerance 14-3, 14-19, 14-20, 14-22, 14-23
  - allocation 14-4
  - curves 14-1
  - function 14-2
  - functions 14-20
  - models 14-2
- Counterbore
  - depth
    - pan head 22-25
    - socket head 22-25
  - symbol 5-13
  - comparison of US and ISO 6-7

- Countersink. *See Double-fixed fastener; Fixed fastener*  
 comparison of US and ISO 6-7  
 symbol 5-13
- Critical features. *See Assembly tolerance models, critical features*
- Critical-to-quality (CTQ) characteristic 1-7, 10-12
- Crosby Quality College 1-4
- Cross product 7-6
- CTQ. *See Critical to Quality (CTQ) characteristic*
- Customer 1-4  
 external 1-4  
 internal 1-4  
 satisfaction 1-3
- Cylinder, pitch. *See Pitch cylinder*
- Cylindrical  
 surface, control of 5-21, 5-22, 5-55  
 tolerance zone 5-14
- Cylindricity tolerance 5-55, 7-12  
 analysis of 9-25  
 symbol 5-13  
 with average diameter 5-56
- D**
- D-shaped feature. *See Bounded feature*
- Data eXchange Format (DXF) 16-19
- Data Management 16-12
- Data Points 18-4
- Database Format Standards 16-19
- Datum 5-6, 5-61, 5-69  
 accuracy 5-95  
 angled. *See Angled datum*  
 axis 5-61, 5-65, 5-69, 5-95, 5-97, 5-102, 5-108, 5-116, 5-136, 5-137, 5-140, 5-141, 5-143, 5-160  
 comparison of US and ISO 6-16  
 candidate. *See Candidate datum*  
 comparison of US and ISO 6-15, 6-16, 6-17, 6-18  
 degrees of freedom 5-63, 5-116  
 feature 5-61  
 angled. *See Angled feature*  
 identification 5-65  
 selection 5-61  
 subject to size variation 18-2  
 surrogate/temporary 5-64  
 symbol 5-13, 5-65  
 symbol placement 5-65, 5-66  
 unstable (rocking) 5-89  
 from a feature pattern 5-100, 18-19  
 generating line as  
 comparison of US and ISO 6-17  
 hyphenated co-datums. *See Hyphenated co-datums*  
 implied. *See Implied datum*  
 letter  
 comparison of US and ISO 6-17  
 mathematically defined surface  
 comparison of US and ISO 6-17  
 origin from. *See Origin from a datum reference frame*  
 paths. *See Assembly tolerance models, datum paths*  
 plane 5-61, 5-69, 5-91, 5-112  
 point 5-61, 5-161  
 precedence 5-14, 5-63, 5-68, 5-69. *See also Degrees of freedom*  
 reference 5-61  
 reference frame (DRF) 5-6, 5-61, 5-69, 7-8  
 candidate. *See Candidate datum reference frame*  
 displacement 5-80, 5-81, 5-83  
 establishing 5-62  
 general note 5-164  
 multiple. *See Multiple DRFs*  
 origin from 5-69, 5-101  
 simultaneous/separate requirements. *See Simultaneous/separate requirements*  
 using in a tolerance analysis. *See Assembly tolerance models datum reference systems*  
 sequence  
 comparison of US and ISO 6-17  
 simulation/simulator 5-68, 5-89, 5-99. *See also True Geometric Counterpart (TGC)*  
 sequence 5-69  
 symbol  
 placement 5-65, 5-66  
 target. 5-91  
 application 5-91, 5-97  
 any feature 5-97  
 feature of size 5-95  
 math-defined feature 5-99  
 revolute 5-97  
 stepped surfaces 5-97

- dimensions 5-94
- identification of 5-92
- interdependency of 5-95
- switchable precedence 5-99
- symbol 5-13, 5-92
- types of 5-92
- target line
  - comparison of US and ISO 6-17
- Defects
  - absence of 1-1
  - assembly 11-1, 11-2, 11-3, 11-13, 11-15
    - comparison of variation models 9-22, 9-23
    - RSS 9-17
  - calculating
    - assembly 11-15, 13-21
    - comparison of GD&T 21-10
    - part/component 11-10
    - using GD&T 21-1
  - fabrication 11-3
  - machine uncertainty 20-4
  - modeling with Poisson 10-8
  - part/component 11-10
  - per million opportunities (dpmo) 17-3
    - cost of poor quality 1-9
  - per opportunity (dpo) 17-3
  - per unit (DPU) 10-9, 17-3
    - estimating yield 10-10
    - how to calculate 21-1
    - Six Sigma measurement 1-7
  - rate 1-8
  - Six Sigma philosophy 1-7
  - Six Sigma quality 10-12
  - weighting methodology 17-7. *See also Tolerance allocation by scaling/resizing/weight factor*
- Degrees of freedom 5-72, 7-8. *See also Assembly tolerance models degrees of freedom; Datum degrees of freedom*
- Deming, W. Edwards 1-2
  - 14 points 1-2
  - Deming Prize 1-2
- Department of Defense (DoD) 5-2
- Depth symbol 5-13
  - comparison of US and ISO 6-8
- Derived
  - element 5-38
  - median line 5-38, 5-39. *See also Straightness tolerance, derived median plane/line control* 5-15
  - median plane 5-38, 5-39. *See also Straightness tolerance, derived median plane/line control* 5-15
- Design
  - engineering driven 2-2
  - for assembly 5-6
  - for assembly (DFA) 2-5
  - for manufacturability (DFM) 2-5
  - inspection driven 2-2
  - process driven 2-2
  - requirements. *See Performance requirements*
- Detail drawings 4-3
- DFA. *See Design for assembly (DFA)*
- DFM. *See Design for manufacturability (DFM)*
- Diameter
  - average. *See Average diameter*
  - spherical. *See Spherical diameter*
  - symbol 5-13, 5-16
    - application of 5-14
    - comparison of US and ISO 6-8
- Digital Equipment Corporation (DEC) 1-6
- Dimension 4-25
  - assembly 13-3
  - auxiliary
    - comparison of US and ISO 6-10
  - basic. *See Basic dimension*
  - chains 15-4
  - component 13-2, 13-3, 13-16
  - controlled 13-8
  - decimal value
    - inch 5-48, 5-49
    - millimeter 5-48, 5-49
  - dependent 13-2
  - independent 13-2
  - limit. *See Limit dimensioning*
  - loop. *See Vector loop. See Loop diagram*
  - nominal. *See Nominal dimension*
  - origin symbol 5-13, 5-112, 5-163
  - path. *See also Loop diagram*
  - paths 15-4
  - redundant 13-8
  - reference 5-18
  - theoretically exact
    - comparison of US and ISO 6-7
- Dimensional management 2-10
  - future of 26-12
  - process 2-8, 2-10

- system 2-10
  - team 2-4
  - Dimensioning
    - and tolerancing 3-1, 3-2, 3-4, 3-6, 3-8
    - methods
      - baseline. *See Baseline dimensioning*
      - chain. *See Chain dimensioning*
      - fundamental rules. *See Fundamental rules*
      - limit dimensioning. *See Limit dimensioning*
      - limits and fits. *See Limits and fits*
      - plus and minus tolerancing. *See Plus and minus tolerance*
      - polar coordinate. *See Polar coordinate system*
      - rectangular coordinate. *See Rectangular coordinate system*
  - Dimensionless print 16-15
  - Dimensions. *See Dimension*
  - Discrimination 18-3
  - Displacement, DRF. *See Datum reference frame (DRF) displacement*
  - Disposition of profile tolerance zone. *See Profile tolerance, disposition of zone*
  - Distribution 10-2
    - Beta. *See Beta distribution*
    - binomial. *See Binomial distribution*
    - Cauchy. *See Cauchy distribution*
    - Exponential. *See Exponential distribution*
    - fitting 15-8
    - function 8-5. *See also Probability distribution function*
    - zone 8-6
  - Gamma. *See Gamma distribution*
  - Gaussian. *See Gaussian distribution*
  - Hypergeometric. *See Hypergeometric distribution*
  - information 15-11
  - Johnson. *See Johnson distribution*
  - Lambda. *See Lambda distribution*
  - Laplace. *See Laplace distribution*
  - Logistic. *See Logistic distribution*
  - Lognormal. *See Lognormal distribution*
  - manufacturing. *See Manufacturing distribution*
  - non normal. *See Non normal distribution*
  - normal. *See Normal distribution*
  - Pearson. *See Pearson distribution*
  - Poisson. *See Poisson distribution*
  - type of 8-3
  - uniform. *See Uniform distribution*
  - Weibull. *See Weibull distribution*
  - DoD. *See Department of Defense (DoD)*
  - Dot product 7-6
  - Double-fixed fastener 22-4, 22-23
    - calculation
      - clearance hole 22-11
      - countersink diameter 22-11
      - head height 22-11
    - examples 22-4
    - formula 22-11
    - sizes/tolerances
      - clearance hole diameter 22-23, 22-24
      - countersink diameter 22-23, 22-24
      - nonfloating nut plate 22-23
      - tapped hole 22-23
  - dpmo. *See Defects per million opportunities (dpmo)*
  - dpo. *See Defects per million opportunities (dpmo)*
  - DPU. *See Defects per unit (DPU)*
  - Drawing
    - GD&T 5-6
    - history 4-2
    - interpretation 4-1
    - number 4-14
    - scale of a 4-14
    - status 4-30
    - title 4-13
  - DRF. *See Datum reference frame*
  - DRSS. *See Dynamic Root Sum of the Squares (DRSS)*
  - Dynamic Root Sum of the Squares (DRSS) 15-6, 15-7
    - allocation 11-20, 11-23, 11-26
  - Dynamic RSS
    - allocation. *See Dynamic Root Sum of the Squares (DRSS) allocation*
- ## E
- E-mail 16-14
  - Each
    - element 5-108
    - radial element 5-108
  - Electronic
    - automation 16-3



- mail 16-14
  - Elliptical cylinder 7-11
  - Encapsulated PostScript (EPS) 16-22
  - Engineering driven design 2-2
  - English language to control part features 5-11
  - Envelope 5-27
    - (Taylor) principle. *See Taylor Principle*
    - actual mating. *See Actual mating envelope*
    - actual minimum material. *See Actual mating/minimum material envelope*
    - boundary of perfect form. *See Boundary of perfect form*
  - Equal
    - bilateral tolerance 4-15, 4-28, 9-5
      - converting an external feature at LMC to 9-31
      - converting an external feature at MMC to 9-30
      - converting an internal feature at LMC to 9-30
      - converting an internal feature at MMC to 9-29
    - precedence datums. *See Hyphenated co-datums*
  - Error sources 20-2
  - Estimated Mean Shift analysis 9-23
  - Estimates of manufacturability 10-1
  - Evolution of quality 1-2
  - Experimental drawing 4-30
  - Exponential distribution 10-6
  - Extension
    - (projection) lines 5-14, 5-51, 5-65
      - comparison of US and ISO 6-8
      - of principle 5-4, 5-59, 5-82, 5-88
  - Extent of profile tolerance 5-145, 5-150
  - External/internal features of size 5-10
- F**
- FAQ (Frequently Asked Question) 5-3, 5-4, 5-9, 5-10, 5-11, 5-48, 5-60, 5-74, 5-76, 5-88, 5-91, 5-92, 5-94, 5-95, 5-97, 5-102, 5-103, 5-114, 5-132, 5-136, 5-138, 5-143, 5-144, 5-150, 5-162
  - Fastener
    - double-fixed. *See Double-fixed fastener*
    - fixed. *See Fixed fastener*
    - floating. *See Floating fastener*
  - Feature 5-9
    - axis 5-38, 5-41
    - bounded. *See Bounded feature*
    - center plane 5-38, 5-41
    - center point 5-38, 5-41
    - control frame 5-14
      - comparison of US and ISO 6-8
      - placement 5-14, 5-15
      - reading 5-16
    - D-shaped. *See Bounded feature*
    - datum. *See Datum feature*
    - factoring method 17-7
    - nonsize. *See Nonsize feature*
    - of size
      - internal/external. *See External/internal features of size*
    - pattern. *See Pattern of features*
    - relating tolerance zone framework (FRTZF) 5-130
    - rotation 4-23
    - spherical. *See Spherical feature*
  - File Transfer Protocol (FTP) 16-14
  - FIM. *See Full Indicator Movement (FIM)*
  - FIR. *See Full Indicator Runout (FIR)*
  - First-angle projection 4-16
  - Fit, clearance. *See Fixed fastener formula; Floating fastener formula; Mating parts; Maximum Material Condition (MMC), when to apply; Virtual condition boundary*
  - Fits, limits and. *See Limits and fits*
  - Five Sigma rule of thumb 17-6
  - Fixed and floating fastener. *See Fixed fastener; Floating fastener*
  - Fixed fastener 22-1, 22-4, 23-4
    - calculation
      - assembly shift 23-5
      - clearance hole diameter 22-10
      - counterbore diameter 22-10
    - double. *See Double-fixed fastener*
    - examples 22-3
    - formula 22-10, 23-7
    - projected tolerance zone. *See Projected tolerance zone*
    - sizes/tolerances
      - clearance hole diameter 22-21, 22-22
      - counterbore hole diameter 22-21, 22-22
      - countersink diameter 22-21, 22-22
      - floating nut plate 22-21

- head height 22-26
- nonfloating nut plate 22-21
- tapped hole 22-21
- tolerance analysis of 23-7
- Flat
  - head screw
    - calculating head height 22-26
    - pattern layout drawing 4-9
  - Flatness tolerance 5-52, 7-13
    - analysis of 9-25
    - comparison of US and ISO 6-13
    - derived median plane 5-40, 5-52
    - for a width-type feature 5-31, 5-46, 5-52
    - per unit area 5-58
    - single planar surface 5-52
    - symbol 5-13
- Flaws 4-29
- Floating and fixed fastener. *See Fixed fastener; Floating fastener*
- Floating fastener 22-1, 22-4, 23-4
  - calculation
    - clearance hole diameter 22-8
    - counterbore diameter 22-9
  - examples 22-2
  - formula 22-8
  - sizes/tolerances
    - clearance hole diameter 22-19, 22-20
    - counterbore hole diameter 22-19, 22-20
    - floating nut plate 22-20
    - tolerance analysis of 23-8
- Ford Motor Company 10-11
- Forgings/castings. *See Castings/forgings*
- Form
  - qualifying notes
    - comparison of US and ISO 6-14
  - control. *See Form tolerance*
- Form tolerance 5-50, 7-9. *See also Levels of control, Level 2: overall form*
  - analysis of 9-25
  - circularity (roundness). *See Circularity (roundness) tolerance*
  - comparison of US and ISO 6-11, 6-13, 6-14
  - cylindricity. *See Cylindricity tolerance*
  - flatness. *See Form tolerance*
  - limits of size. *See Levels of control, Level 2: overall form; Limits of size*
  - profile. *See Profile tolerance*
  - runout. *See Runout tolerance*
  - straightness. *See Straightness tolerance*
  - when to use 5-60
- Formula
  - double-fixed fastener. *See Double-fixed fastener formula*
  - fixed fastener. *See Fixed fastener formula*
  - floating fastener. *See Floating fastener formula*
  - resultant condition 5-38
  - virtual condition 5-31, 5-32, 5-128
- Frame
  - basic dimension. *See Basic dimension frame*
  - datum feature symbol. *See Datum feature symbol*
  - datum reference. *See Datum reference frame*
  - feature control. *See Feature control frame*
- Framework of boundaries/zones 5-127
  - feature relating (FRTZF). *See Feature relating tolerance zone framework (FRTZF)*
  - pattern locating (PLTZF). *See Pattern locating tolerance zone framework (PLTZF)*
- Free state
  - application 5-20, 5-57
  - symbol 5-13, 5-16
  - comparison of US and ISO 6-9
- Freedom, degrees of. *See Datum degrees of freedom; Degrees of freedom*
- FRTZF. *See Feature Relating Tolerance Zone Framework (FRTZF); Feature relating tolerance zone framework (FRTZF)*
- FTP. *See File Transfer Protocol (FTP)*
- Full
  - Indicator
    - Movement (FIM) 5-139
    - Runout (FIR) 5-139
  - sections 4-19
- Functional
  - gaging 5-25, 19-1
  - hierarchy 5-63, 5-71
  - requirements 5-20, 5-38
  - Gages 19-1
- Fundamental
  - levels of control. *See Levels of control*
  - rules 5-18
- Future of
  - academia 26-7

dimensional management 26-1, 26-12  
 dimensioning and tolerancing 26-13  
 GD&T 5-164, 26-1, 26-5, 26-12  
 global standards and business perspective  
 26-9  
 research 26-4  
 software tools 26-2, 26-13  
 standards 26-2  
   dimensioning/tolerancing 26-10, 26-13  
   metrology 26-11  
 tolerance analysis 26-2, 26-5  
 tolerancing 26-7  
   in academics 26-2, 26-12  
   in business 26-2

## G

Gage repeatability and reproducibility (GR&R)  
 25-1  
 analysis 25-1

Gaging  
 functional 5-25  
 tolerances 19-3  
 virtual 5-44

Galvin, Bob 1-6

Gamma distribution 10-6

Gap equation. *See Performance requirements; Tolerance analysis equations, vector loop (2-D)*

1-D 9-7, 11-7

2-D/3-D 12-4, 12-11, 13-13

Gauss, Karl Frederick 10-2

Gaussian distribution 21-8

GD&T. *See Geometric Dimensioning and Tolerancing (GD&T)*

Gears/splines 5-11

General

  dimensions 4-25, 4-26

  tolerance

    comparison of US and ISO 6-9

Generation templates 16-7

Geometric

  characteristic symbol 5-14, 5-15

  Dimensioning and Tolerancing (GD&T) 2-6, 3-1, 3-9, 5-2, 8-2

  advice 5-3

  analysis of 9-24

  certification of GD&T professionals 5-3

  future of. *See Future of GD&T*

  instant 5-163  
   overview 5-9  
   symbols 5-11, 5-13, 5-15  
   what is it? 5-2  
   when to use 5-8, 5-9  
   why to use 5-4

  Product Specification 7-1

  tolerance 8-3

  tolerancing 3-11, 3-12

  variation. *See Variation, geometric*

Geometrical

  Product Specification (GPS)

    Masterplan 6-4

GIDEP 7-2

GO gages 19-1

GR&R. *See Gage repeatability and reproducibility (GR&R)*

Graphical inspection analysis 18-2

Groove 5-10, 5-138, 5-142, 5-144

## H

Half sections 4-19

Harry, Mikel J. 1-6

Histogram 10-2

Hog Out Parts 16-17

Hole

  angled. *See Angled feature*

  counterbored. *See Counterbore*

  countersunk. *See Countersink*

  pattern verification 18-5

  slotted. *See Slotted hole*

Horizontal loop 9-4. *See also Assembly tolerance models, vector loops*

HPGL 16-20

Hypergeometric distribution 10-8

Hypertext Markup Language (HTML) 16-21

Hyphenated co-datums 5-103, 5-104, 5-140, 5-141

## I

IBM 1-6

IGES 16-20

Implied

  90° angle dimension 5-19

  90° basic angle dimension 5-19, 5-87, 5-104, 5-109

  basic dimension 5-116

## I-12 Index

datum 5-117  
parallelism/perpendicularity 5-104  
symmetry 5-116  
Independency Principle 5-29  
Indication of limited length/area. *See Limited length/area indication*  
Indicator movement/swing 5-141, 5-142  
Injection molded plastic 16-17  
Inner/outer boundary 5-46  
    using in a tolerance analysis 9-28  
Inspection driven design 2-2  
Instant GD&T 5-163, 5-164  
Integrated  
    design process 1-9  
    product team 1-5, 10-12  
Interchangeability 8-1  
Internal/external features of size. *See External/internal features of size*  
International  
    Organization for Standardization (ISO) 1-10, 4-2, 5-3, 6-2, 7-14, 8-2, 8-10  
    standards 6-2  
    Telephone and Telegraph Corporation 1-4  
Internet 16-13  
Interrupted surface 5-10  
Intranet 16-13  
ISO. *See International Organization for Standardization (ISO)*  
ISO 9000 1-10  
Isometric views 4-24

## J

Johnson distribution 15-8  
Joint Photographic Experts Group (JPEG) 16-22  
Juran Institute, Inc. 1-3  
Juran, Joseph 1-3

## K

Key characteristics 2-6, 2-10. *See also Assembly tolerance models, key characteristics*  
Kinematic joints. *See Assembly tolerance model, kinematic joints*  
    degrees of freedom 13-5  
    incoming 13-8  
    outgoing 13-8

    path across 13-7  
    types 13-5  
        cylindrical slider 13-6, 13-7  
        edge slider 13-5, 13-7  
        parallel cylinders 13-6, 13-7  
        planar 13-7  
        planar joint 13-6  
Kinematic model 15-4  
Kodak 1-6  
Kurtosis 15-6

## L

Lagrange Multiplier 14-3  
    Method 14-7  
Lambda distribution 15-8  
Language 8-2  
"Language of management is money" 1-3  
Laplace distribution 10-6  
Lay 4-29  
Layout Gaging 18-2  
Least  
    Material Condition (LMC) 5-23  
        for feature control 5-25  
        symbol 5-13, 5-16  
        when to apply 5-15, 5-23, 5-28, 5-32, 5-47  
        zero tolerance at. *See Zero tolerance at MMC/LMC*  
    squares 7-11  
Levels of control 5-20  
    Level 1: size and 2-D form 5-20, 5-48  
    Level 2: overall form 5-20, 5-26, 5-50  
    Level 3: orientation 5-20, 5-33, 5-103  
    Level 4: location 5-20, 5-34, 5-113  
Limit dimensioning 5-48, 5-49  
Limited length/area indication 5-57, 5-143  
Limits  
    and fits 5-48  
    and fits symbol 5-48  
    of size 5-20. *See also Rules, #1 boundary. See Size limit boundary*  
    circularity control. *See Circularity (roundness) tolerance control by limits of size*  
    cylindrical feature 5-21  
    width-type feature 5-22  
Line  
    center. *See Center line*

chain. *See Chain line*  
 derived median. *See Derived median line*  
 extension. *See Extension lines*  
 phantom. *See Phantom line*  
 precedence 4-23  
 profile. *See Profile tolerance of a line*  
 profile of a. *See Profile tolerance, of a line*

## Linear

tolerance 3-3, 4-15. *See also Plus and minus tolerance*  
 comparison with GD&T 3-9, 22-5

LMC. *See Least Material Condition (LMC)*

## Lobes

circularity control 5-54, 5-55  
 concentricity control 5-157, 5-160  
 cylindricity control 5-55

Location tolerance. *See Levels of control, Level 4: location*

Logistic distribution 10-6

Lognormal 21-2

distribution 10-6  
 approximation to Normal distribution 10-7  
 transforming values 10-7

Loop. *See Vector loop*

closed. *See Closed loop*  
 diagram. *See Assembly tolerance models, vector loops*  
 equation. *See Tolerance analysis equations, vector loop (2-D)*  
 horizontal. *See Horizontal loop*  
 open. *See Open loop*  
 vertical. *See Vertical loop*

Lower specification limit 8-2

## M

Machined part 4-6, 4-7  
 drawing 4-4

Machining processes 14-5

Malcolm Baldrige National Quality Award 1-2, 1-9, 2-3

design and production processes are coordinated 1-9

differs from ISO 9000 1-10

Motorola 1-6

Manufacturing

guidelines 16-15

process 9-5, 9-15

capability data. *See Process capability*

*data*

distributions 21-2

variation. *See Variation sources, process*

process capability. *See Process capability*

Master Model 16-10

Theory 16-4

Material condition 5-23. *See also Least*

*Material Condition (LMC); Maximum Material Condition (MMC); Regardless of Feature Size (RFS)*

analysis of 9-27

least. *See Least Material Condition (LMC)*

maximum. *See Maximum Material Condition (MMC)*

modifier symbol 5-14, 5-16, 5-24

modifiers

analysis of 21-2

proper use of 24-10

regardless of feature size. *See Regardless of Feature Size (RFS)*

Math Standard

ASME Y14.5.1M (the "Math Standard"). *See American National Standards, ASME Y14.5M (the "Math Standard")*

Mathematically defined surface 5-75, 5-89

comparison of US and ISO 6-17

datum targets for 5-99

profile control for 5-147

Mathematization 7-4

Mating parts 5-26, 5-28, 5-33, 5-34, 5-36, 5-128. *See also Fixed fastener*

*formula; Floating fastener*

*formula; Maximum Material Condition*

*(MMC), when to apply; Virtual condition*

Maximum

inscribed circle 7-11

Material Condition (MMC) 5-23, 21-2

for feature control 3-12, 5-25

symbol 5-13, 5-16

when to apply 5-15, 5-23, 5-31, 5-47

zero tolerance at. *See Zero tolerance at MMC/LMC*

MBNQA. *See Malcolm Baldrige National Quality Award*

MCS. *See Monte Carlo Simulation (MCS)*

Mean 8-2, 10-3

gap. *See Gap equation*

Measured value 7-7

- Measurement  
 methods analysis 20-1  
 temperature 5-19
- Median  
 line  
 derived. *See Derived median line*  
 plane  
 comparison of US and ISO 6-18  
 derived. *See Derived median plane*
- Method of System Moments (MSM) 15-6, 15-7, 15-8, 15-9, 15-11
- Metrology 5-3, 5-23, 7-3
- Minimum circumscribed circle 7-11
- Minimum cost. *See Tolerance allocation by cost minimization*
- Minimum radial separation 7-11
- Minimum stock protection. *See Least Material Condition (LMC), when to apply*
- Minitab 12 10-4, 10-7
- Modern manufacturability 1-5
- Modified Root Sum of the Squares (MRSS)  
 analysis 9-18
- Modifying symbol 5-14, 5-16, 5-24  
 when to apply 5-15
- Monte Carlo Simulation (MCS) 15-6, 15-8, 15-9
- Motorola 1-6  
 Baldrige Award 1-6  
 Six Sigma is a trademark of 1-10
- MRSS. *See Modified Root Sum of the Squares (MRSS)*
- MSM. *See Method of System Moments (MSM)*
- Multiple  
 Datum Structures 19-14  
 DRFs 5-103
- N**
- National  
 Science Foundation (NSF) 7-3  
 Standards 6-27
- Native database 16-19
- NOGO gages 19-2
- Nominal dimension 5-1
- Non normal distribution 10-6
- Nonrigid part 5-19  
 average diameter. *See Average diameter*  
 comparison of US and ISO 6-9  
 restraint. *See Restraint of nonrigid part*
- Nonsize feature 5-10, 5-75
- Normal distribution 15-8
- Normality 8-3
- Note 4-29  
 all over. *See All over note*  
 drawing 4-3  
 for "instant" GD&T 5-164  
 for runout control 5-144  
 general datum reference frame 5-164  
 restraining. *See Free state; Restraint of nonrigid part*  
 to modify tolerance 5-144, 5-162
- NSF. *See National Science Foundation (NSF)*
- Number of places 5-10  
 symbol 5-13
- Numerical notation  
 comparison of US and ISO 6-9
- Nut plates 22-14. *See also Double-fixed fastener; Fixed fastener; Floating fastener*
- O**
- O-ring groove 5-48, 5-64, 5-144. *See also Groove*
- Obsolete drawing 4-30
- Offset sections 4-19
- Open loop. *See Assembly tolerance models, open loop*
- Optimizing  
 unstable (rocking) datum feature 5-89
- Optimum acceptance fraction 14-8
- Order of precedence. *See Datum precedence*
- Organize for quality improvement 1-3
- Orientation control. *See Orientation tolerance*
- Orientation tolerance 5-103. *See also Levels of control, Level 3: orientation*  
 analysis of 9-26  
 angularity. *See Angularity tolerance*  
 applications table 5-110, 5-111  
 applied to line elements 5-107  
 comparison of US and ISO 6-19  
 datum application 5-104  
 how to apply 5-103  
 parallelism. *See Parallelism tolerance*  
 perpendicularity. *See Perpendicularity tolerance*  
 when to use 5-109  
 with tangent plane. *See Tangent plane*

- zero. *See Zero tolerance at MMC/LMC orientation*
- Origin
  - dimension origin symbol. *See Dimension origin symbol*
  - from datum reference frame 5-61, 5-69, 5-101
- Outer/inner boundary 5-46
  - using in a tolerance analysis 9-28
- Outline, profile. *See Basic profile*
- Over limited length/area. *See Limited length/area indication*
- P**
- Paper gaging 18-1
  - advantages and disadvantages 18-2
- Paperless/electronic environment 5-147, 16-2
- Parallelism tolerance 5-95, 5-104
  - analysis of 9-26
  - symbol 5-13
- Pareto principle 1-3
- Partial views 4-23
- Pattern
  - Locating Tolerance Zone Framework (PLTZF) 5-129
  - of features 5-100, 5-127
    - composite tolerance for positional. *See Positional tolerance, pattern control, composite*
    - profile. *See Profile tolerance, composite*
    - radial. *See Radial feature pattern*
- PDF. *See Portable Document Format (PDF)*
- Pearson distribution 15-8
- Per area/length unit 5-57, 5-58
- Percent
  - containment 8-5
  - contribution chart 13-23
- Perfect form. *See Boundary of perfect form*
  - boundary at LMC. *See Boundary of perfect form at LMC*
  - boundary at MMC. *See Boundary of perfect form at MMC*
  - not required. *See Boundary of perfect form not required*
- Performance
  - expected assembly 11-15
  - requirements 9-1, 9-2, 13-10, 13-11, 13-12, 24-2
- Perpendicularity tolerance 5-104, 5-105
  - analysis of 9-26
  - symbol 5-13
- Personal computer 7-2
- Phantom line 5-92, 5-147
- Piecepart tolerance. *See Tolerance, piecepart*
- Pin
  - diamond 24-6
  - parallel-flats 24-6
- Pins. *See Alignment pins*
- Pitch cylinder 5-11
- Pitch diameter rule
  - comparison of US and ISO 6-10
- Placement
  - datum feature symbol. *See Datum symbol placement*
  - feature control frame. *See Feature control frame placement*
- Plane
  - center. *See Center plane*
  - datum. *See Datum plane*
  - derived median. *See Derived median plane*
  - feature center. *See Feature center plane*
  - median
    - comparison of US and ISO 6-18
  - mutually perpendicular 5-69, 5-70
  - tangent. *See Tangent plane*
  - tolerance. *See Tolerance plane, sweeping*
- PLTZF. *See Pattern Locating Tolerance Zone Framework (PLTZF)*
- Plus and minus tolerance 5-9, 5-49. *See also Angle plus and minus tolerance; Linear tolerance*
  - comparison with GD&T 3-9, 22-5
- Point
  - center. *See Center point*
  - datum. *See Datum point*
- Poisson distribution 10-8, 10-9
- Polar coordinate system 5-116, 5-124
- Population 8-1
  - parameter zone 8-5
- Portable Document Format (PDF) 16-22
- Positional control. *See Positional tolerance*
- Positional tolerance 5-113
  - analysis of 9-27
  - comparison of US and ISO 6-20, 6-21, 6-22, 6-23
  - datum application 5-116

- for a bounded feature 5-126, 5-153
  - for coaxiality to a datum 5-69, 5-137
  - how to apply 5-114
  - pattern control
    - coaxial/coplanar features 5-136
    - composite 5-129
    - single-segment 5-127
  - stacked segments 5-134, 5-136
  - symbol 5-13
  - true position. *See True position*
  - with implied datums 5-117
  - with projected tolerance zone 5-117
    - at LMC 5-120
    - at MMC 5-119
    - at RFS 5-119
  - zero. *See Zero tolerance at MMC/LMC positional*
- Precedence, datum. *See Datum precedence*
- switchable. *See Datum target switchable precedence*
- Principle
- Envelope (Taylor). *See Taylor Principle*
  - extended/extension. *See Extension of principle*
  - of Independency
    - comparison of US and ISO 6-11
- Probabilities
- additive 10-7
- Probability distribution function 10-9
- Probe 7-2
- Process
- analysis 18-4
  - capability 15-10
    - data 11-3, 15-10, 24-7. *See also Manufacturing process capability data*
    - defined by industry 10-10
    - for generating holes 24-6
    - index (Cp) 10-10, 10-11, 15-11
      - relative to process centering (Cpk) 10-12
    - indices 8-2
    - long-term 1-8, 24-7
    - matrix 20-1
    - models 17-1
    - short-term 1-7, 24-7
  - changes to the design or manufacturing 10-1
  - driven design 2-2
  - manufacturing. *See Manufacturing process*
  - selection 14-15
  - shift 10-12
  - variation 26-4
- Product 1-3
- Data Management (PDM) 16-13
  - development process 16-3
  - documentation 16-11
  - financial success 10-1
  - performance 10-1
  - product feature 1-3
  - product satisfaction 1-3
  - vault 16-12
- Profile
- basic. *See Basic profile*
  - control. *See Profile tolerance*
  - outline. *See Basic profile*
- Profile tolerance 5-145, 5-147
- abutting zones 5-153
  - analysis of 9-34
  - application 5-146
  - basic profile. *See Basic profile*
  - bilateral 5-147
    - comparison of US and ISO 6-25, 6-26
  - composite 5-154
    - analysis of 9-36
      - for a pattern of features 5-154, 5-155
      - for a single feature 5-156
  - controlling the extent of 5-150
  - datum application 5-149
  - disposition of zone 5-145, 5-147
  - equal bilateral
    - analysis of 9-34
  - equal-bilateral 5-147
  - extent of. *See Extent of profile tolerance*
  - for a combination of attributes 5-153
  - for coplanarity 5-154
  - for form control 5-60, 5-153
  - for math-defined surfaces 5-147
  - for stepped surfaces 5-97
  - how to apply 5-145
  - of a line 5-149
  - of a surface 5-145, 5-149
  - symbol 5-13
  - unequal bilateral 5-147
    - analysis of 9-35
  - unilateral 5-147
    - analysis of 9-35
- Projected tolerance zone 22-15
- application 5-117, 5-119



comparison of US and ISO 6-21  
 comparison with no projection 22-16  
 comparison without projected zone 22-16  
 symbol 5-13, 5-16  
 Projection view 4-16  
 Proportional scaling 14-11  
 Push pin versus fixed pin gaging 19-20

## Q

Quality 1-1  
 control 1-1  
 Crosby Quality College 1-4  
 evolution of 1-2  
 improvement 1-1  
   organize for 1-3  
 is free 1-4  
 planning 1-1  
 prediction models 17-3  
 Six Sigma approach 1-6  
 Quantitative measure of manufacturability 1-9  
 Question (Frequently Asked Question). *See*  
*FAQ*

## R

Radial feature pattern 5-134  
 Radius 5-10  
   controlled. *See Controlled radius*  
   spherical. *See Spherical radius*  
   symbol 5-13, 5-16, 5-58  
   comparison of US and ISO 6-10  
   tolerance 5-58  
   zone 5-58  
 Rapid prototypes 16-18  
 Receiver Gages 19-1  
 Rectangular coordinate system 5-122  
 Reference  
   dimension 5-18  
   application 5-18  
   comparison of US and ISO 6-10  
   symbol 5-13, 5-16  
   frame (DRF)  
   multiple 5-103  
 Regardless of Feature Size (RFS) 21-2  
   comparison of US and ISO 6-10  
   for feature control 3-11, 5-38  
   when to apply 5-15, 5-47  
 Release procedures 16-12  
 Removed section 4-22  
 Repeatability 7-2  
 Requirements. *See Performance requirements*  
   functional. *See Functional requirements*  
   simultaneous/separate. *See Simultaneous/  
   separate requirements*  
 Research 7-3  
 Resize. *See Tolerance allocation by scaling/  
   resizing/weight factor*  
   factor. *See Tolerance allocation by scaling/  
   resizing/weight factor*  
 Restraint  
   of minimum material envelope. *See Actual  
   minimum material envelope, restraint of*  
   of nonrigid part 5-20  
   using a note 5-146  
 Restrictive tolerance  
   comparison of US and ISO 6-14  
 Resultant condition 23-2  
   boundary 5-37  
   LMC 5-38  
   MMC 5-37, 5-38  
   using in a tolerance analysis 9-28, 23-2  
 Revision blocks 4-16  
 Revolute 5-10, 5-97  
   control  
   with circularity 5-53  
   with concentricity 5-158, 5-160  
   with runout 5-144  
   datum targets applied to 5-97  
 Revolved section 4-22  
 RFS. *See Regardless of feature size (RFS)*  
 RMS (root-mean-square) deviation index 8-4  
 Rocking. *See Datum feature, unstable (rocking)*  
 Root Sum of the Squares (RSS) 9-12, 13-  
   13, 13-20, 13-21, 15-6, 15-7  
   allocation  
   by cost minimization 14-14  
   by manufacturing processes 11-18, 11-  
   19, 11-23  
   by scaling/resizing/weight factor 14-11  
   analysis 9-12, 12-2  
   expression 13-20  
 Rotation 24-1  
 Rotational shift tolerance 18-16  
 Roughness 4-29  
 Roundness. *See Circularity*  
 RSS. *See Root Sum of the Squares (RSS)*

## Rules

- #1 5-27, 5-28
  - comparison of US and ISO 6-11
  - exceptions. *See Boundary of perfect form not required; Independency principle*
- #2
  - comparison of US and ISO 6-10
- 2a
  - comparison of US and ISO 6-10
- assembly tolerance models. *See Assembly tolerance models, modeling; Assembly tolerance models, modeling rules*
- Five Sigma rule of thumb. *See Five sigma rule of thumb*
- for pattern control
  - composite 5-131
  - stacked single segment 5-136
- fundamental. *See Fundamental rules*
- pitch diameter
  - comparison of US and ISO 6-10
- Runout control. *See Runout tolerance*
- Runout tolerance 5-138
  - analysis of 9-33
  - circular 5-141. *See also Circular runout tolerance*
  - datum application 5-140
  - general note for 5-144
  - how to apply 5-139
  - over a limited length/area 5-143
  - total. *See Total runout tolerance*
  - when to use 5-144

## S

- Schroeder, Richard 1-6
- Screw threads 5-11
- Secondary datum feature 19-5
- Section views 4-16
- Semantics 8-2
- Sensitivity 9-37, 12-2, 12-4, 12-11, 12-12, 13-13, 13-15, 13-16, 14-10, 15-7
  - analysis 12-2, 13-24
- Separate
  - gaging requirement 19-9
  - requirement. *See Simultaneous/separate requirements*
- Sequence
  - assembly 5-64

- datum simulation. *See Datum simulation/simulator sequence*
- Sequential geometric product definition 19-12
- Sheet metal
  - part 4-8
- Sheetmetal 16-16
- Shift. *See Datum reference frame*
- Sigma value 1-8, 17-3
- Simulation/simulator
  - actual mating envelope. *See Actual mating envelope*
  - actual minimum material envelope. *See Actual minimum material envelope*
  - datum. *See Datum simulation/simulator*
- Simultaneous
  - engineering teams 2-4
  - gaging requirement 19-9
    - comparison of US and ISO 6-22
- Simultaneous/separate requirements 5-86, 5-133, 5-136
  - gaging. *See Separate gaging requirement*
  - note to override 5-87, 5-88, 5-132, 5-133
  - with composite tolerance 5-132
- Six Sigma
  - Academy 1-6
  - approach to quality 1-6, 17-1
  - capability 1-8, 20-1, 20-22
  - critical-to-quality (CTQ) characteristic 1-7
  - degradation in short-term performance 1-7
  - design 10-14
  - history of 1-6
  - initiative 26-2
  - long-term perspective 1-7
  - long-term process capability 1-8, 24-7
  - predicting assembly quality 11-1
  - process capability. *See Process capability*
  - quality method 2-3
  - Research Institute (SSRI) 1-6
  - short-term process capability 1-7, 24-7
  - sigma value 1-8
  - statistic 1-7
  - techniques 17-2, 17-3
  - tolerance allocation. *See Tolerance allocation by manufacturing processes*
  - trademark of Motorola 1-10
- Size 22-22
  - actual mating. *See Actual mating size*

- actual minimum material. *See Actual minimum material size*
- actual minimum material local. *See Actual minimum material local size*
- and tolerance 22-19
- basic 5-48
- control
  - comparison of US and ISO 6-11
- datums
  - analysis of 9-36
- feature of. *See Feature of size*
- limit 5-48
  - boundary 5-20, 5-26
  - spine. *See Spine*
- maximum material/least material condition 5-23
- Regardless of. *See Regardless of feature size (RFS)*
- resultant condition 5-38. *See also Resultant condition*
- virtual condition 5-31, 5-32. *See also Virtual condition*
- Sketch 4-30
- Skewness a 15-6
- Slotted hole 5-126
- Smith, Bill 1-6
- Softgaging 5-44
- Software 7-3
- SPC (Statistical Process Control) 5-18, 15-10
- Specification, production inspection 8-1
- Spherical
  - boundary 5-14
  - diameter
    - symbol 5-16, 5-38
    - tolerance zone 5-38
  - feature, circularity tolerance for 5-54, 5-55
  - feature, positional tolerance for 5-35
  - radius 5-10, 5-59
    - symbol 5-13, 5-16
    - tolerance zone 5-59
- Spine 5-20, 7-9
  - cylindrical feature 5-21
  - width-type feature 5-21
- Splines. *See Gears/splines*
- Splines/gears. *See Gears/splines*
- Square symbol 5-13, 5-18, 5-57, 5-92
  - comparison of US and ISO 6-11
- SRSS analysis. *See Static Root Sum of the Squares (SRSS) analysis*
- SSRI. *See Six Sigma Research Institute (SSRI)*
- Standard deviation 8-2, 10-3, 11-3, 11-16, 11-17, 11-20, 11-21, 11-22, 11-26
- Standards 8-1
  - American National. *See American National Standards*
  - committee 26-7
  - ISO. *See International Organization for Standardization (ISO)*
- Static
  - Root Sum of the Squares (SRSS) 15-6, 15-7
    - analysis 11-23
  - RSS analysis. *See Static Root Sum of the Squares (SRSS) analysis*
- Statistical
  - moment 15-6, 15-7
  - Process Control (SPC) 2-6, 5-18, 8-9
  - tests 10-4
  - tolerance 8-1, 24-6
    - allocation 11-14, 11-17, 24-6
    - application 5-18, 8-2, 11-25, 24-6, 24-15, 24-19, 24-22, 24-25, 24-28
    - symbol 5-13, 5-16
    - symbol, comparison of US and ISO 6-11
    - zone 8-5
- Statistician's job 1-2
- Statistics 10-1
- STEP 16-20
- Stepped surfaces 5-97
- Stereolithography (SLA) 16-18
- STL 16-21
- Stock
  - protection. *See Least Material Condition (LMC), when to apply*
  - Rule #1 exemption 5-29
- Straightness tolerance
  - analysis of 9-25
  - at LMC 5-28, 5-32, 5-46
  - at MMC 5-30, 5-45
  - at RFS 5-40
  - comparison of US and ISO 6-14
  - derived median plane/line 5-45, 5-46, 5-52
  - for a cylindrical feature 5-31, 5-40, 5-52
  - for a flat surface 5-51
  - for a surface (line) element 5-51
  - per length unit 5-57
  - symbol 5-13

## Surface

- element control 5-15, 5-108
- interrupted 5-10
- mathematically defined. *See Mathematically defined surface*
- of revolution 7-10
- profile. *See Profile tolerance of a surface*
- profile of a. *See Profile tolerance of a surface*
- stepped. *See Stepped surfaces*
- texture 4-28

## Surrogate/temporary datum feature 5-64

## Sweeping balls

- for a feature of size 5-21
- for a spherical feature of size 5-22
- for a width-type feature of size 5-21

## Symbol 5-11, 11-25

- all around. *See All around symbol*
- comparison of US and ISO 6-7
- angularity tolerance. *See Angularity tolerance symbol*
- arc length. *See Arc length symbol*
- basic dimension
  - comparison of US and ISO 6-7
- between. *See Between symbol*
- comparison of US and ISO 6-7
- circularity tolerance. *See Circularity (roundness) tolerance symbol; Circularity tolerance symbol*
- concentricity tolerance. *See Concentricity tolerance symbol*
- controlled radius. *See Controlled radius symbol*
- comparison of US and ISO 6-7
- counterbore. *See Counterbore symbol*
- counterbore/spotface
  - comparison of US and ISO 6-7
- countersink. *See Countersink symbol*
- comparison of US and ISO 6-7
- cylindricity. *See Cylindricity tolerance symbol*
- datum feature. *See Datum feature symbol*
- datum target. *See Datum target symbol*
- depth. *See Depth symbol*
- depth/deep
  - comparison of US and ISO 6-8
- diameter. *See Diameter symbol*
- comparison of US and ISO 6-8

dimension origin. *See Dimension origin symbol*

flatness. *See Flatness tolerance symbol*

form and proportions 5-12, 5-13

free state. *See Free state symbol*

comparison of US and ISO 6-9

Least Material Condition (LMC). *See Least Material Condition (LMC) symbol*

Maximum Material Condition (MMC). *See Maximum Material Condition (MMC) symbol*

number of places. *See Number of places symbol*

parallelism. *See Parallelism tolerance symbol*

perpendicularity tolerance. *See Perpendicularity tolerance symbol*

position tolerance. *See Positional tolerance symbol*

profile tolerance. *See Profile tolerance symbol*

projected tolerance zone. *See Projected tolerance zone symbol*

radius. *See Radius symbol*

comparison of US and ISO 6-10

reference dimension. *See Reference dimension symbol*

scale and proportions. *See Symbol form and proportions*

spherical radius. *See Spherical radius symbol*

square. *See Square symbol*

comparison of US and ISO 6-11

statistical tolerance. *See Statistical tolerance symbol*

comparison of US and ISO 6-11

straightness. *See Straightness tolerance symbol*

symmetry tolerance. *See Symmetry tolerance symbol*

tangent plane. *See Tangent plane symbol*

comparison of US and ISO 6-12

total runout tolerance. *See Total runout tolerance*

Symmetry control. *See Symmetry tolerance*

Symmetry tolerance 5-156

about a plane 5-159, 5-161

about an axis (concentricity) 5-10 *See also Concentricity tolerance*

analysis of 9-33

comparison of US and ISO 6-24  
 datum application 5-159  
 implied 5-116  
 symbol 5-13  
 when to use 5-162  
 Syntax 8-2  
 Systems engineering analyses 1-5

**T**

Tabulated tolerances 5-18  
 Tagged Image File Format (TIFF) 16-22  
 Taguchi, Genichi 1-4  
 Taguchi's  
   Loss Function 1-5  
   quadratic cost function 8-4  
 Tangent plane 5-104  
   symbol 5-13, 5-16, 5-105  
   application 5-104, 5-105  
   comparison of US and ISO 6-12  
 Target  
   datum. *See Datum target*  
   value 1-5, 8-2  
 Taylor  
   Envelope 4-25  
   Principle 4-25  
     comparison of US and ISO 6-11  
   series approximation 15-7  
 Temperature for measurement. *See Measurement temperature*  
 Template  
   design 16-7  
   features 16-8  
   part 16-8  
 Templates  
   Analyses 16-9  
   Documentation 16-9  
 Temporary/surrogate datum feature 5-64  
 Tertiary datum feature 19-5  
 TGC. *See True geometric counterpart (TGC)*  
 Theoretically exact  
   dimension  
     comparison of US and ISO 6-7  
   position  
     comparison of US and ISO 6-23  
 Theory of probability 1-2  
 Thermal expansion 24-1  
 Third-angle projection 4-16

Threads 5-11  
 Three-Dimensional Verification 18-8  
 TIR. *See Total Indicator Runout (TIR)*  
 Tolerance 22-22  
   3-sigma 9-15, 9-23, 13-20  
   accumulation 13-20  
   allocation 8-9, 11-2  
     1-D 14-1  
     2-D/3-D 14-8  
   by cost minimization 14-1, 14-12, 14-13, 14-14  
   by manufacturing processes 11-2, 11-5, 11-13, 14-15, 24-2  
   by scaling/resizing/weight factor 9-10, 9-16, 9-19, 14-10, 14-11  
   by weight factors. *See Tolerance allocation by scaling/resizing/weight factor*  
   DRSS. *See Dynamic Root Sum of the Squares (DRSS) allocation*  
   LaGrange multipliers 14-3  
   optimization 14-1, 14-12  
   process selection 14-15  
   proportional scaling. *See Tolerance allocation by scaling/resizing/weight factor*  
   RSS. *See Root Sum of the Squares (RSS) allocation*  
   sensitivities. *See Sensitivity*  
   statistical. *See Statistical tolerance allocation*  
   true cost 14-8  
   worst case. *See Worst Case allocation*  
 allocation data  
   cost 14-18  
   empirical cost functions 14-2, 14-18  
   process tolerances 14-5  
 analysis 8-10, 9-1  
   1-D 9-2, 15-5  
   2-D 12-1, 13-12, 15-5  
   3-D 15-5  
   accumulation 13-20  
   CAD-based systems 13-27  
   derivatives 13-15, 13-16  
   equations, explicit 12-8, 12-10, 13-2, 13-13  
   equations, implicit 13-2, 13-15  
   equations, linear 13-15, 13-16  
   equations, matrix 13-15, 13-16  
   equations, nonlinear 13-15, 13-19

- equations, vector loop (2-D) 13-13, 13-14, 13-16, 13-19
- Estimated Mean Shift. *See Estimated Mean Shift analysis*
- gap 13-12. *See also Tolerance analysis equations, vector loop*
- MRSS. *See Modified Root Sum of the Squares (MRSS) analysis*
- percent contribution 13-22
- percent rejects 13-20
- predicted rejects 13-21
- process 9-2
- relative rotations 13-14
- RSS. *See Root Sum of the Squares (RSS); Root Sum of the Squares (RSS) analysis*
- sensitivities. *See Sensitivity*
- SRSS. *See Static Root Sum of the Squares (SRSS) analysis*
- steps in 9-2, 11-6, 11-14, 12-4, 13-12
- upper/lower limits 13-22
- virtual prototype 13-27
- worst case. *See Worst case analysis*
- angular 4-15
- assembly 13-11, 13-12
- assigning 13-11
- assignment. *See Tolerance allocation*
- bilateral. *See Equal bilateral tolerance; Unequal bilateral tolerance*
- bonus. *See Bonus tolerance*
- boundary 5-14
- composite. *See Composite tolerance*
- positional 5-129
- design
  - insensitive to variation 13-24, 13-25
  - modifying geometry 13-24
  - requirements. *See Performance requirements*
  - tightening/loosening tolerances 13-23
- double-fixed fastener. *See Double-fixed fastener tolerance*
- equal bilateral. *See Equal bilateral tolerance*
- extent of 5-119, 5-150
- fixed fastener. *See Fixed fastener tolerance*
- floating fastener. *See Floating fastener tolerance*
- form. *See Form tolerance*
- general
  - comparison of US and ISO 6-9
  - influence of 13-11
  - linear 3-3, 4-15
  - material condition basis. *See Material condition*
  - model 15-3, 15-11
    - steps in analyzing. *See Tolerance analysis, steps in*
    - steps in creating (1-D) 9-4
    - steps in creating (2-D/3-D) 12-4, 13-4
  - optimization 15-9
  - orientation. *See Orientation tolerance*
  - over a limited length. *See Limited length/area indication*
  - per unit area/length. *See Per area/unit length*
  - piecepart 9-11
  - placement in feature control frame 5-14
  - plane, sweeping 5-149
  - plus and minus. *See Plus and minus tolerance*
  - positional. *See Positional tolerance*
  - profile. *See Profile tolerance*
  - progression 3-1, 3-6
  - representation 4-28
  - restrictive
    - comparison of US and ISO 6-14
  - runout. *See Runout tolerance*
  - stacks 9-1
  - statistical. *See Statistical tolerance*
  - straightness. *See Straightness tolerance*
  - strategy
    - combination linear and geometric 3-5
    - geometric 3-6, 3-11, 3-12
    - linear 3-2, 3-8
  - symmetry. *See Symmetry tolerance*
  - synthesis 8-9
  - tabulated. *See Tabulated tolerances*
  - unequal bilateral. *See Unequal bilateral tolerance*
  - unilateral. *See Unilateral tolerance*
  - zero at MMC/LMC. *See Zero tolerance at MMC/LMC*
- zone
  - abutting. *See Profile tolerance, abutting zones*
  - bidirectional. *See Bidirectional positional tolerance*
  - central. *See Central tolerance zone*

- comparison of US and ISO 6-12
- framework (FRTZF and PLTZF). *See Feature relating tolerance zone framework (FRTZF); Pattern locating tolerance zone framework (PLTZF)*
- projected. *See Projected tolerance zone*
- shape 5-14, 5-15, 5-38
- size 5-14
- tapered 5-121
- wedge shaped. *See Wedge-shaped tolerance zone*
- Total
  - Indicator Runout (TIR) 5-139
  - Quality Management (TQM) 1-3
  - runout tolerance 5-143, 5-144
    - for a cone 5-143
    - symbol 5-13
- TQM. *See Total Quality Management*
- Transition
  - between profile zones 5-153
- Translation 24-1
- True
  - cost 14-8
  - geometric counterpart (TGC) 5-67, 5-68
    - restraint of 5-68, 5-75
  - types 5-74
    - adjustable-size 5-75
    - fixed size 5-77
    - nonsize 5-75
    - restrained 5-75
    - unrestrained 5-75
  - position 5-37
    - comparison of US and ISO 6-23
    - methods for establishing 5-114
- Type of distribution. *See Distribution, type of*
- U**
  - Uncertainty 7-7, 20-2
  - Unequal bilateral tolerance 4-28
  - Uniform distribution 10-8
  - Unilateral
    - profile tolerance zone 5-147
      - analysis of 9-35
    - tolerance 4-28, 5-49, 5-50. *See also Unilateral profile tolerance zone*
  - Unit vector 7-5
  - Unstable (rocking) datum feature. *See Datum feature, unstable (rocking)*
  - Upper specification limit 8-2
  - US Government Standards 6-28
  - US Standards 6-2
- V**
  - Variable
    - data 10-2
    - process capability models 17-3
  - Variance 15-6
  - Variation 9-7
    - accumulation 13-2, 13-10
    - geometric
      - in a tolerance model. *See Assembly tolerance models, geometric variations*
    - measurement and reduction 2-7, 2-11
    - propagation 13-2, 13-10
    - simulation tolerance analysis 2-7, 2-11
    - sources
      - assembly 13-2, 13-8, 13-16
      - component 13-2, 13-8, 13-16
      - dependent 13-3, 13-8
      - dimensional 13-2, 13-3
      - geometric 13-2, 13-10
      - independent 13-3, 13-10
      - kinematic 13-2
      - process 13-2, 13-20, 15-4
      - rotational 13-10
      - surface waviness 13-10
      - translational 13-10
    - versus tolerance 13-13
  - Vector
    - addition 7-5
    - loop. *See Assembly tolerance models, vector loops*
    - model 14-10
    - loop equations. *See Tolerance analysis equations, vector loop*
    - subtraction 7-5
  - Vectors 7-5, 13-6, 13-7
  - Vertical loop 9-4. *See also Assembly tolerance models, vector loops*
  - View
    - auxiliary. *See Auxiliary view*
    - isometric. *See Isometric views*
    - partial. *See Partial views*
    - projection. *See Projection view*
      - comparison of US and ISO 6-12
    - section. *See Section views*

Virtual

- condition 5-35, 5-36, 5-68, 5-107, 5-121, 5-128, 23-2
- boundary 5-30, 5-43
  - for form. *See Levels of control, Level 2: overall form*
  - for location. *See Levels of control, Level 4: location*
  - for orientation. *See Level of control, Level 3: orientation*
- datum
  - comparison of US and ISO 6-18
- LMC 5-32
- MMC 5-31, 5-35
- using in a tolerance analysis 9-28, 23-2
- gaging 5-44
- Reality Modeling Language (VRML) 16-20
- VRML. *See Virtual Reality Modeling Language (VRML)*

- Zero tolerance at MMC/LMC 5-35
  - orientation 5-36, 5-107
  - positional 5-36
- Zone 4-4
  - tolerance. *See Tolerance zone comparison of US and ISO* 6-12

**W**

- Wall thickness. *See Least Material Condition (LMC), when to apply; Resultant condition*
- Waviness 4-29
- Wedge-shaped tolerance zone 5-109, 5-112
- Weibull distribution 10-6
- Weight Factors. *See Tolerance allocation by scaling/resizing/weight factor*
- Width-type feature 5-10
- Workmanship 5-8
- Workspace 16-12
- World Wide Web (WWW) 16-13
- Worst case 11-26, 15-6
  - allocation 11-5, 11-24, 14-11, 14-13, 24-6
  - analysis 9-9, 12-2, 13-12, 13-20
  - expression 13-20
  - tolerance 8-1

**Y**

- Y14.5.1M, ASME (the "Math Standard"). *See American National Standards, ASME Y14.5.1M (the "Math Standard")*
- Y14.5M, ASME. *See American National Standards, ASME Y14.5M*

**Z**

- Z table 10-4, 10-14